



Certificate Record

Customer	Class	File Number
BriskHeat Corp	2872-01	116197_0_000
4800 Hilton Corporate Drive,	HEATERS-Cable and Cable Sets	
Columbus	TIEM ENG-Gable and Gable Gets	
OH		
USA		
43232		

To the requirements of CSA Std. 130-03:

Heating Cable Sets (usages G, W, S) – Constant Wattage parallel heating cable, type "FE-CAB", with FEP insulation, FEP inner jacket, shielding, and optional FEP overall jacket, rated 120V ac and 240V ac, maximum continuous exposure temperature of 232°C max, 20A per circuit maximum, for use with supply lead and end connection kits: FE-CAB-KC, FE-CAB-UC, FE-CAB-SK, FE-CAB-EP, FE-CAB-LP.

- for embedded floor warming, soil heating, snow melting, roof de-icing, up to 12W/ft max.
- for pipe & vessel tracing, up to 18W/ft max.

Notes:

- 1. Installation in accordance with the Canadian Electrical Code Part I.
- 2. Manufacturer's minimum recommended installation temperature: -30°C.

Obtained from the CSA Online Certified Product Listing

Date: April 12, 2016

Signature:

Full Name:

Douglas R. Dietz

Position:

Vice President of Engineering