



Expanding the line of side plate construction rotameters, King introduces its 7459 Series. These models feature a 250 mm scale borosilicate glass tube with Aluminum side plates and a polycarbonate shield. Connections are vertical FNPT, 316L Stainless Steel.

DESCRIPTION

- Metering Tube**
Borosilicate Kinglass®
- Internal Components**
Standard: 316L SS
- Fitting Material**
Standard: 316L SS
- Inlet/Outlet Fittings**
NPT, vertical connection:
Sizes 3 & 4: 1/2" FNPT
Size 5: 3/4" FNPT
Size 6: 1" FNPT
Size 8 & 9: 1 1/2" FNPT
- O-Ring**
Standard: Viton®
Optional: Buna N, EPR, Kalrez®

PERFORMANCE

- Capacities**
Water 0.22 to 100 GPM
Air 0.9 to 350 SCFM
- Scale**
250 mm (10")
direct reading, detachable
- Accuracy**
± 2% of full scale flow
- Turndown**
10:1
- Repeatability**
0.5%
- Max Temperature**
316L SS fittings
Gases 250° F (121° C)
Liquids 200° F (93° C)

- Maximum Pressure**
Sizes 3 & 4: 350 psig
Size 5: 175 psig
Size 6, 8 & 9: 125 psig
- Ambient Temperature**
33° F to 125° F (1° C to 52° C)

OPTIONS

- Certified Calibrations**
Conform to ISA RP 16.6
- Scales**
Any volumetric unit

Order Number	Dimension (Inches)		Connection Size (FNPT)
	A	B	
31W - 46W	17	2.5	1/2"
51W - 56W	17	2.5	3/4"
61W - 613W	17	2.5	1"
84W - 98W	19	4.5	1 1/2"

SPECIFICATIONS:

Order No.	GPM Water	Order No.	SCFM Air	Float No.	Float Type	Press Drop (W.C.)	Tube Size	Tube No.
31W	0.220	31A	.9	3/8-LPG-01	LP	—	3/8-20-G-10	3G
32W	0.315	32A	1.4	3/8-SLG-01	SL	2	3/8-20-G-10	3G
33W	0.640	33A	2.7	3/8-SLG-02	SL	7	3/8-20-G-10	3G
41W	0.77	41A	3.4	1/2-LPG-01	LP	6	1/2-32-G-10	4G
42W	1.02	42A	4.4	1/2-LPG-02	LP	10	1/2-32-G-10	4G
43W	1.20	43A	5.0	1/2-GVG-01	GV	0	1/2-32-G-10	4G
44W	1.44	44A	6.1	1/2-GSG-01	GS	15	1/2-32-G-10	4G
45W	1.92	45A	8.5	1/2-SLG-01	SL	28	1/2-32-G-10	4G
46W	2.26	46A	10.2	1/2-SLG-02	SL	41	1/2-32-G-10	4G
51W	1.1	51A	4.5	3/4-LPG-01	LP	1	3/4-28-G-10	5G
52W	2.4	52A	10.0	3/4-GVG-01	GV	4	3/4-28-G-10	5G
53W	3.0	53A	12.0	3/4-GSG-01	GS	5	3/4-28-G-10	5G
54W	3.3	54A	13.2	3/4-GVG-02	GV	6	3/4-28-G-10	5G
55W	4.0	55A	16.4	3/4-GSG-02	GS	6	3/4-28-G-10	5G
56W	5.2	56A	22.0	3/4-SLG-01	SL	18	3/4-28-G-10	5G
61W	6.9	—	—	1-LPG-02	LP	4	1-32-G-10	6G
62W	9.8	—	—	1-SLG-01	SL	8	1-32-G-10	6G
63W	12.6	—	—	1-SLG-02	SL	13	1-32-G-10	6G
64W	6.7	64A	27.0	1-LPP-01	LP	4	1-40-P-10	6P
65W	7.4	65A	30.0	1-GVP-01	GV	6	1-40-P-10	6P

Order No.	GPM Water	Order No.	SCFM Air	Float No.	Float Type	Press Drop (W.C.)	Tube Size	Tube No.
66W	8.5	66A	35.0	1-GVP-02	GV	8	1-40-P-10	6P
67W	10.4	67A	42.5	1-GSP-01	GS	10	1-40-P-10	6P
68W	11.6	68A	46.5	1-GVP-03	GV	15	1-40-P-10	6P
69W	12.0	69A	50.0	1-GSP-02	GS	14	1-40-P-10	6P
610W	15.6	610A	63.0	1-GSP-03	GS	24	1-40-P10	6P
611W	21.6	611A	100.0	1-SLP-01	SL	61	1-40-P10	6P
612W	27.5	—	—	1-SLP-02	SL	85	1-40-P10	6P
613W	34.5	—	—	1-SLP-03	SL	110	1-40-P10	6P
84W	17.0	84A	70.0	11/2-GVP-01	GV	10	8P - 11/2-32-P-10	8P
85W	21.2	85A	87.0	11/2-GVP-02	GV	13	8P - 11/2-32-P-10	8P
86W	22.2	—	—	11/2-GSP-01	GS	14	8P - 11/2-32-P-10	8P
87W	24.8	87A	102.0	11/2-GVP-03	GV	18	8P - 11/2-32-P-10	8P
88W	28.5	—	—	11/2-GSP-02	GS	20	8P - 11/2-32-P-10	8P
89W	35.0	—	—	11/2-GSP-03	GS	24	8P - 11/2-32-P-10	8P
94W	41.5	94A	170.0	2-GVP-01	GV	20	9P - 2-30-P-10	9P
95W	58.0	95A	240.0	2-GSP-01	GS	25	9P - 2-30-P-10	9P
96W	65.0	96A	270.0	2-GSP-02	GS	30	9P - 2-30-P-10	9P
97W	85.0	97A	350.0	2-SLP-00	SL	40	9P - 2-30-P-10	9P
98W	100.0	—	—	2-SLP-01	SL	50	9P - 2-30-P-10	9P

Note: Tubes with the designation "G" have rib-guided floats. Tubes designated "P" have pole-guided floats

ORDERING:

Use the following guide to determine the specific product number you require.

7	4	5		*	
Meter Series	Order Number See Specifications Table	Fitting Material 316L SS - 2	O-ring Material EPR - 1 Buna-N - 2 Viton® - 3 Kalrez® - 4	Scale Millimeter - 1 GPM Water@70°F - 2 LPM Water@70°F - 3 SCFM Air@STP - 4 SLPM Air@STP - 5 Non standard - 6	
		* Only use this box with order numbers 610W thru 613W. Otherwise leave blank.			